

Argox X-2000+

The X-2000+ is a versatile printer with a unique "stand-alone" operation feature. It comes with 1 MB of flash memory and a standard PS2 interface to connect a PC keyboard or scanners for independent data input. No extra cost for KDU or printer controller is required.

This printer is easy to use and maintain. Its built-in flash ROM enables users to quickly download firmware and easily switch programming languages. A full-function front panel with a multilingual LCD display simplifies installation, configuration, and operation. No PC is required, making this a true "stand-alone" operation printer.



[Request a quote](#)

Specification	
Printing method	Direct thermal & thermal transfer
Printing resolution	203 (8 dots/mm) dpi
Printing speed	2 ~ 6 ip (51 ~ 152 mm/s)
Printing length	0.5" ~ 4.5" (13mm ~ 114.3mm)
Printing width	1.0" ~ 4.09" (25mm ~ 104 mm)
Memory	2MB DRAM 1MB Flash ROM
CPU type	32 bit RISC microprocessor
Media sensor	Reflective Transmissive
Display	LCD 2-line x 16 display, LED indicators x 3
Communication interface	Centronics parallel RS-232 serial PS-2 keyboard wedge
Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper. Max width 4.3" (110 mm) Min width 1.0" (25 mm) Min length 0.4" (10 mm) Thickness .0025"~.01" Max roll capacity 8" (.0635mm (203 mm) ~.254mm) OD Core size 1.5"~3.0" (38mm~76 mm) ID
Ribbon	Wax, Resin, Wax/Resin, Ribbon width - 1.3", 2.5", 3.3", 4.3" (33 mm, 64 mm, 84 mm, 109 mm) roll - max 1182' (360 M) Core size - ID 1" core (25 mm) Ribbon length - max 1182' (360 M) Core size - ID 1" core (25 mm)
Compact size	W 9.8" x H 10.2" x L 16.0" (W 250 x H 260 x L 410 mm)
Weight	24.6 lbs (11 kgs)
Power source	110/220 VAC ±10%, 50/60 Hz
Agency listing	CE, UL, CUL, FCC class A
Operation environment	40°C ~ 100°C (4°F ~ 38°F) 10~90% non condensing
Optional items	Cutter, Dispenser kit (including internal rewinder), ArgoNet print server, USB interface, Flash memory card, ArgoKee Standalone KDU

Argox X-3000+

The X-3000+ printer is ideal for applications that require small labels or textile media. Its standard 300dpi print head ensures superior printing quality for first-class characters, graphics and barcodes.

The X-3000+'s combination of features and power provides greater productivity and cost advantage to the user.

The X-3000+ is also bundled with free Win98/2000/NT/XP drivers and WYSIWYG softwares (ArgoBar) for ready-to-use operation



[Request a quote](#)

Specification	
Printing method	Direct thermal & thermal transfer
Printing resolution	300 dpi (12 dots/mm)
Printing Speed	2 ~ 6 ips (51 ~ 152 mm/s)
Printing length	0.5" ~ 30" (13mm ~ 762mm)
Printing width	1.0" ~ 4.25" (25mm ~ 108 mm)
Memory	2MB DRAM 1MB Flash ROM
CPU type	32 bit RISC Microprocessor
Media sensor	Reflective Transmissive
Display	LCD display, 2-line x 16 LED indicators x 3
Communication interface	Centronics parallel RS-232 serial PS-2 keyboard wedge
Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper. Max width 4.3" (110 mm) Min width 1.0" (25 mm) Min length 0.4" (10 mm) Thickness .0025" ~ .01" (.0635mm ~ .254mm) Max roll capacity 8" (203 mm) Core size 1.5" ~ 3.0" (38mm ~ 76 mm) ID
Ribbon	Wax, Wax/Resin, Resin Ribbon width - 1.3", 2.5", 3.3", 4.3" (33 mm, 64 mm, 84 mm, 109 mm) Ribbon roll - max 1182' (360 M) Core size - ID 1" core (25 mm)
Compact size	W 9.8" x H 10.2" x L 16.0" (W 250 x H 260 x L 410 mm)
Weight	24.6 lbs (11 kgs)
Power source	110/220 VAC iO 10%, 50/60 Hz
Agency listing	CE, UL, CUL, FCC class A
Operation environment	40°C ~ 100°C (4°F ~ 384°F) 10~90% non condensing
Optional items	Cutter, Dispenser kit (including internal rewinder), ArgoNet print server, USB interface, Flash memory card, ArgoKee Standalone KDU