

AT-870

RF-ID



Main Features

- Lightweight rugged Industry Design with Compact sizes.
- Marvel Latest CPU.
- Robust wireless option WiFi, GSM/GPRS/EDGE or CDMA EVDO/20001X and Bluetooth connectivity.
- Integrated Imager/Laser Scanner allows various Barcode Reading.
- Built in GPS with integrated Antenna.
- Microsoft's latest Operating System (Windows CE 5.0/6.0)
- RF-ID integrated UHF(866MHz 954 Mhz), HF(13.56MHz)
Built in



SP TRADERS
SRD Infotech Pvt.Ltd.

C/2, Avanti Apartment, L.M.Road,Navagaon,
Dahisar-(W), Mumbai-400 068.

Mobile: +919820429309 / +919321026721

Ring: +91-022 28950137

E_MAIL: info@srdinfotech.com ;

spraders99@rediffmail.com

www.srdinfotech.com

SPECIFICATIONS



Processor	Marvel PXA270 520MHz Marvel PXA320 820MHz (Option)
Memory	128MB RAM/256MB ROM
Operating System	Windows CE 5.0, Windows CE 6.0 (Option) Windows Mobile 6.0 (option by order),
Display	3.5 " TFT LCD, 256K color LCD QVGA resolution (240W x 320L) with backlight
User Interface	Keyboard buttons and Touch screen - Numeric key Hands Free Speaker, Microphone/Receiver Headset Port
Standard Communications	USB 1.1 Host & Client RS232 interface (Connector Option), DC Jack Ethernet(via Cradle) Option
Wireless Communications (Optional)	<ul style="list-style-type: none">• WLAN/PAN Option• WLAN Option-802.11b/g-CDMA EVDO or 2000 1X-Bluetooth v2.0, Class II (SPP)-GSM/GPRS/EDGE-WCDMA (Option by order)
RF-ID (Optional)	HF 13.56 Mhz (ISO 15693, 14443A/B, MIFARE) UHF 866 - 954 Mhz (EPC Class 1 GEN2)
Barcode Applications (Optional)	1D Laser Scanner Option, 2D Imager Option
Camera(Optional)	1.3 megapixel Fixed Focus with flash
GPS (Optional)	GPS Receiver with integrated Antenna
Expansion Slot	1 Micro SD slot, 1 slim slot
Power	3000 mAh Lithium Polymer main Battery Pack 4400 mAh Lithium Ion Pack with Gun Option 100 mAh Lithium Polymer Back-up Battery
User Environment	-20°C to 50°C Operating Temperature -30°C to 60°C Storage Temperature (w/o Battery) 95% non-condensing Humidity 1.5 meters to polished concrete, IP54 Sealing
Accessories and Options	Single Slot Cradle (with Ethernet Option) Vehicle Cradle, Sync Cable, Battery Charger Gun Handle (with 4400 mAh Battery Option) Belt clip, 4 Slot Cradle (Option by Order)
Dimensions	146 x 74 x 26 (L x W x H mm)
Weight	270g- 330g (according to option)

AT-870



Main Features

- Lightweight rugged Industry Design with Compact sizes.
- Marvel Latest CPU.
- Robust wireless option WiFi, GSM/GPRS/EDGE or CDMA EVDO/20001X and Bluetooth connectivity.
- Integrated Imager/Laser Scanner allows various Barcode Reading.
- Built in GPS with integrated Antenna.
- Microsoft's latest Operating System (Windows CE 5.0/6.0)



SP TRADERS
SRD Infotech Pvt.Ltd.

C/2, Avanti Apartment, L.M.Road, Navagaon,
Dahisar-(W), Mumbai-400 068.

Mobile: +919820429309 / +919321026721

Ring: +91-022 28950137

E. MAIL: info@srdinfotech.com ;

sptraders99@rediffmail.com

www.srdinfotech.com

SPECIFICATIONS



Processor	Marvel PXA270 520MHz Marvel PXA320 820MHz (Option)
Memory	128MB RAM/256MB ROM
Operating System	Windows CE 5.0, Windows CE 6.0 (Option) Windows Mobile 6.0 (option by order),
Display	3.5 " TFT LCD, 256K color LCD QVGA resolution (240W x 320L) with backlight
User Interface	Keyboard buttons and Touch screen - Numeric key Hands Free Speaker, Microphone/Receiver Headset Port
Standard Communications	USB 1.1 Host & Client RS232 interface (Connector Option), DC Jack Ethernet(via Cradle) Option
Wireless Communications (Optional)	<ul style="list-style-type: none">• WLAN/PAN Option• WLAN Option-802.11b/g-CDMA EVDO or 2000 1X-Bluetooth v2.0,-GSM/GPRS/EDGEClass II (SPP)-WCDMA (Option by order)
Barcode Applications (Optional)	1D Laser Scanner Option, 2D Imager Option
Camera(Optional)	1.3 megapixel Fixed Focus with flash
GPS (Optional)	GPS Receiver with integrated Antenna
Expansion Slot	1 Micro SD slot, 1 slim slot
Power	3000 mAh Lithium Polymer main Battery Pack 4400 mAh Lithium Ion Pack with Gun Option 100 mAh Lithium Polymer Back-up Battery
User Environment	-20°C to 50°C Operating Temperature -30°C to 60°C Storage Temperature (w/o Battery) 95% non-condensing Humidity 1.5 meters to polished concrete, IP54 Sealing
Accessories and Options	Single Slot Cradle (with Ethernet Option) Vehicle Cradle, Sync Cable, Battery Charger Gun Handle (with 4400 mAh Battery Option) Belt clip, 4 Slot Cradle (Option by Order)
Dimensions	146 x 74 x 26 (L x W x H mm)
Weight	270g- 330g (according to option)